

VERIFICATION OF COMPLIANCE

No.: GPSD GZES2207014001PV01

Applicant: Shenzhen SOFARSOLAR Co., Ltd.
11/F., Gaoxinqi Technology Building, No. 67 Area, Xingdong Community,
Xin'an Sub-district, Bao'an District, Shenzhen, Guangdong, China.

Manufacturer: Shenzhen SOFARSOLAR Co., Ltd.
11/F., Gaoxinqi Technology Building, No. 67 Area, Xingdong Community,
Xin'an Sub-district, Bao'an District, Shenzhen, Guangdong, China.

Product Name: Hybrid Inverter (Three Phase)

Model No.: HYD 5KTL-3PH, HYD 6KTL-3PH, HYD 8KTL-3PH;
HYD 10KTL-3PH, HYD 15KTL-3PH, HYD 20KTL-3PH;

Trade Mark: 

Rating: Refer to page 2 and 3.

Protection against Electric Shock: Class I

Degree of Protection: IP 65

Additional Information (if any): Firmware version: V2.00

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: VDE 0126-1-1:2013
(include the requirement of Enedis-PRO-RES_10E:26/06/2020,
VFR:2013, VFR:2014 and VFR:2019.)

as shown in the GZES220701400101

Test Report Number(s):

This Verification of GPSD Compliance has been granted to the applicant based on the results of tests performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards and the General Product Safety Directive 2001/95/EC.


David Guo

Senior Technical Manager

2022-08-02

SGS-CSTC

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>

Member of SGS Group (Société Générale de Surveillance)

No.:

GPSD GZES2207014001PV01

Other information added:

Rating:

Model	HYD 5KTL-3PH	HYD 6KTL-3PH	HYD 8KTL-3PH	HYD 10KTL-3PH	HYD 15KTL-3PH	HYD 20KTL-3PH
PV String Input Data						
Max. DC voltage	1000V					
MPPT voltage range	180V~960V					
Full power MPPT voltage range	250V~850V	320V~850V	360V~850V	220V~850V	350V~850V	450V~850V
Max. input current	12.5A/12.5A	12.5A/12.5A	12.5A/12.5A	25A/25A	25A/25A	25A/25A
Max. short current	15A/15A	15A/15A	15A/15A	30A/30A	30A/30A	30A/30A
Battery Input Data						
Battery voltage range	180V~800V					
Battery voltage range for full load	200V~800V	240V~800V	320V~800V	200V~800V	300V~800V	400V~800V
No. of battery input	1			2		
Nominal charging/discharging power	5000W	6000W	8000W	10000W	15000W	20000W
Rated charging/discharging current	25A	25A	25A	50A (25A/25A)	50A (25A/25A)	50A (25A/25A)
Max. charging/discharging current	25A	25A	25A	50A (25A/25A)	50A (25A/25A)	50A (25A/25A)



David Guo
Senior Technical Manager
SGS-CSTC



2022-08-02

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>
Member of SGS Group (Société Générale de Surveillance)

No.:

GPSD GZES2207014001PV01

Other information added:

Rating:

AC Output Data (On-grid)						
Nominal AC power	5000W	6000W	8000W	10000W	15000W	20000W
Max. AC power output to utility grid	5500VA	6600VA	8800VA	11000VA	16500VA	22000VA
Max. AC power from utility grid	10000VA	12000VA	16000VA	20000VA	30000VA	40000VA
Max. AC current output to utility grid	8A	10A	13A	16A	24A	32A
Rated AC current output to utility grid	7.2A	8.7A	11.6A	14.5A	21.7A	29A
Max. AC Current from utility grid	15A	17A	24A	29A	44A	58A
Nominal output voltage	3/N/PE, 230Vac					
Nominal output frequency	50Hz					
Output power factor	~1(0.8 leading to 0.8 lagging)					
AC Output Data (Back-up)						
Nominal output power	5000W	6000W	8000W	10000W	15000W	20000W
Max. output power	5500VA	6600VA	8800VA	11000VA	16500VA	22000VA
Rated. output current	7.2A	8.7A	11.6A	14.5A	21.7A	29A
Max. output current	8A	10A	13A	16A	24A	32A
Nominal output voltage	3/N/PE, 230Vac					
Nominal output frequency	50Hz					
Output power factor	~1(0.8 leading to 0.8 lagging)					
Operating temperature range	-30°C ~60°C					
Ingress protection	IP65					
Protective class	Class I					
Cooling method	Heat sink	Heat sink	Heat sink	Fan	Fan	Fan



David Guo
Senior Technical Manager
SGS-CSTC



2022-08-02

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>
Member of SGS Group (Société Générale de Surveillance)